

TSD-IP005 IP HD Camera

HD/ Full High Definition

Main Features

- IP Waterproof Camera
- 1/3" Aptian AR0130 CMOS Image sensor
- Hisilicon Hi3518C High performance DSP
- H.264 video compression, support dual stream
- Built-in 2 Mega pixel 2.8~12mm lens
- Built-in Web Server makes it possible for users to visit camera through IE browser,
- Adjust the stream and frame rate according to the bandwidth
- Support video lost, motion detection
- Support self connection to the internet when disconnection happens
- Support 8 users to visit the camera at the same time
- Support remote system upgrade function
- Compatible SDK and client software
- Support IR-CUT
- Support ONVIF



Technical Specification

Model	TSD-IP005
Image Compression Format	H.264
Image sensor	1/3" Aptian AR0130 CMOS
Mini illumination	0.1Lux@F1.2 (color), 0.03 Lux@F1.2 (B/W)
Video resolutions	1280*960 / 640*480 / 320*180
Frame rate	25 FPS
streams	0.1Mbps – 8 Mbps
Motion Detect	Support
Alarm Event	Email / Picture
IR-CUT	Support
Lens	2.8~12mm Manual Zoom 2 Mega pixel
IR Range	42PCS ϕ 5 IR Leds / 40 meters IR distance
Double streams	Support
Safety	Password protection、 User management system

Local Distributor,

GLOBAL TELE COMMUNICATIONS

H.No:3-83/A/106, 1st Floor, Pavani Residency,
Eswar Villas Road, Opp. Bachpan School, Nizampet,
Hyderabad-500090, Telangana State, INDIA. PH:040-65907456,
www.globaltelecomm.co.in, Email: info@globaltelecomm.co.in

Network Interface	RJ-45 10-100 Base T
Network Protocol	TCP/UDP/IP/HTTP/RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
Onvif	Support
Working Condition	0°C – 45°C (32°F–133°F) , 10% - 90%PH
power	Output:12VDC/1A; Input:100–240VAC, 50–60Hz

Local Distributor,

GLOBAL TELE COMMUNICATIONS

H.No:3-83/A/106, 1st Floor, Pavani Residency,
Eswar Villas Road, Opp. Bachpan School, Nizampet,
Hyderabad-500090, Telangana State, INDIA. PH:040-65907456,
www.globaltelecomm.co.in, Email: info@globaltelecomm.co.in