Dealer :

Made in Italy

Newtech Equipment

Newtech Equipment

3D WHEEL ALIGNMENT

(4D TECHNOLOGY)

(Model : NT 3D)

Target : 600 gm only.

SPECIFICATION :

1. HD special industrial camera
2. Mini target
3. LCD Double display data
4. Usable for long wheelbase vehicle adjustment
5. Camera can be replaced with built in compensation reference
6. Many ways of compensation; no push compensation is possible
7. Field installation, no need to calibrate
8. Self-diagnosis and correction function
9. Working efficiency management function
10. Specific environmental adaptivity and fill-in light flash function of cameras
11. All chassis data measurement including wheelbase, wheel track, axle offset and etc
12. Database covering more than 20,000 car models worldwide, intelligent update at any time
13. Beam automatically moves up and down to track the targets
14. Usable with 2-post, 4-post, scissors lifts and pit.

CCD WHEEL ALIGNMENT

(Model : TD5040 / TD5060)

TD5040WD, with two front measuring heads equipped with 4 infra-red CCD sensors and two rear infra-red transmitters, makes it possible to measure all steering angles, operating first on the rear axle and then on the front one.

STANDARD ACCESSARIES :

- 1 control unit with PC, 19” monitor, key-board, printer and battery-charger
- 2 front measuring heads
- 2 rear measuring heads
- STDA33EU four point clamps
- 1 pair of S110A7 turn tables
- 1 brake pedal depressor
- 1 steering wheel lock
- Instruction manual on CD

Newtech Equipment

WHEEL BALANCER

(Model : NT 702)

Technical Data :

Power Supply	220V
Motor Power	0.25 kw
Rim width	1.5” / 12”
Rim Diameter	12” / 24”
Rim Center Hole Diameter	≤145mm
Max. Wheel Diameter	650mm
Balancing Time	7S
Balancing Speed	180rpm
Balancing Precisoin	±1g
Net/Gross Weight	118/146 Kg.
Packing Dimension	850x700x1160mm

WHEEL BALANCER

(Model : NT 986)

Technical Data :

Power Supply	220V
Motor Power	0.25 kw
Rim width	1.5” / 12”
Rim Diameter	12” / 24”
Rim Center Hole Diameter	≤145mm
Max. Wheel Diameter	800mm
Balancing Time	7S
Balancing Speed	180rpm
Balancing Precisoin	±1g
Net/Gross Weight	120/150 Kg.
Packing Dimension	820x820x1100mm

AUTOMATIC TYRE CHANGER

(With Run Flat Attachment)

(Model : NT 622)

Technical Data :

External Rim Clamping	:	10” min. 18” max.
Internal Rim Clamping	:	10” min. 24” max.
Wheel Rim Width	:	10”
Max. Chuck Rotating to Torque	:	100 - 100 kg.
Drive Motor	:	0.75 Kw. / 1 HP 3 Ph. 415 V or 0.75 Kw. / 1 HP 1 PH. 230 V
Bead Breaker Opening	:	13” (325 mm)
Max. Wheel dia.	:	40” (1010 mm)
Bead Breaking	:	16.5 kn at 12 Bar.
Compressed Air required	:	6 to 12 bars.
Floor Space (L x W x H)	:	960 x 730 xc 1560 (in mm)
Net Weight of Machine	:	200 Kgs. Approx.
Gross Weight of Machine	:	230 Kgs. Approx.

AUTOMATIC TYRE CHANGER

(Model : NT 522)

Technical Data :

Outside Clamp	: 10-18”
Inside Clamp	: 12-21”
Tire Width	: 3-12”
Maximum Wheel Diameter	: 960 mm
Working Air Pressure	: 8-10 bar
Turntable Rotation Speed	: 6.5 rpm
Power Supply Voltage	: 220V
Power	: 0.75/1.1 Kw
Noise	: <70dB
CTN Size	: 980 x 760 x 950
Net Weight/Gross Weight	: 179/207

Newtech Equipment

HIGH PRESSURE CAR WASHER (Model : NT 110P)

Technical Data :

Water Output	:	750 ltrs. / hr.
Operating Pressure	:	110 bars/1600 Psi
Motor Rating	:	3 Kw.

Standard Accessories :

High Pressure House, 10 mt.
Spray Lance 500mm long.
High Spray Nozzle. 25°

Extra Accessories :

Spray Nozzle, 0
Spray Lances : 75 mm, 150 mm, 1040 mm
Pressure regulator
Trolley

FULLY AUTOMATIC NITROGEN GENERATOR

(Model : NT 6000)

Nitrogen Generator and Conversion System for Single Tyre Application

- Suit for: Motorcycle, Car
- Converts the tyre to Nitrogen at the touch of a button
- Auto-Start Inflation
- Over Pressure Setting (OPS)
- Single Tyre Application

Technical Data :

Power Supply	:	AC 220V, 50 Hz
Max. Compressed Air Pressure	:	145Psi/10Bar/10Mps
Nitrogen Capacity	:	70L
Nitrogen Producing Speed	:	66L / Min
Auto Tire	:	52 Times/Hour
Measuring Range	:	5-11 OPsi/0-3.88ar/0.3-8 Mps

Newtech Equipment

Automobile Equipments, Tools & Service

Reg. Office Address : 31, Jayma Society, Nr. Satellite Complex, Premchand Nagar Road, Satellite, Ahmedabad-380015. M.: 93271 23141

Factory Unit Address : 16, Aust Mangal Estate, Bhilwas, Nr. Asarwa Bridge, Haripura, Asarwa, Ahmedabad. M.: 94260 68557

Customer Care : 93769 42189 • E-mail : newtechequipment@gmail.com • Website : www.newtech.equipment.in