



## BOND –IWP-03

### **INTERIOUR PRIMIMUM EMULSION PAINTS** **NANO POLYMER FILLED WATER REPELLENT PAINT**

BOND Interior PRIMIMUM Emulsion has a rich and smooth matt finish that ozzes sophistication. It has been fortified with stain guard technology that guards your walls against household stains and ensures easy cleanability. It has a long lasting film that keeps your house as good as new for a long time.

It is designed to protect your walls against unwanted fungus that can cause considerable damage.

It offers a unique range of extra deep colors that helps you highlight your home's features better.

#### ADVANTAGES

- ❖ Excellent water repellency with air permeability.
- ❖ Soil & Stain release property. Mild softening effect .
- ❖ No detrimental influence on color fastness properties
- ❖ Stain proof finish resistant to staining by hydrophilic soils
- ❖ Gives air permeable, water and oil impermeable finish, also gives breathable finish
- ❖ Water based formulations
- ❖ Resistance to Dust, Dirt, Mould, Algee, etc
- ❖ UV Protection
- ❖ Save some electricity due to dry air in the rooms due to NANO POLYMER reduce load for Air-Condition.
- ❖ Low Cleaning and Maintenance requirements.

#### METHOD OF USE:-

**SURFACE PREPARATION:-** (1) Surface should be Dry, clean, even and free from dust, dirt, paint, rust, Algee, grease, soluble salt, or other contaminations. For cleaning use cleaner. Coating should be applied and dried in a dust free environment, preferably in clean room conditions.

#### PRECAUTIONS :-

Do not apply when temperature is less than 10 oC or if the temperature might drop to this level within 4 hrs. of applications.

Do not over thin or over extend the brush.

Stire well and stain before use. Tinted paints need thorough shaking immediately after addition as well as before use.

#### SAFETY FEATURES :-

Kindly refer MSDS for this products which gives detailed informations on safety measures while handling the paint, which is available on request. Store the container with the lid tightly closed in an upright position, in a cool dry place. Keep out the rich of children's and away from eatables.

May be harmful if swallowed. In case of ingestion seek immediate medical attention. When eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical; advice. Immediately wash skin with soap and plenty of water. Get medical attention of irritation develops or persists.

Do not breath vapor or spray. It is recommended to wear suitable nose pad during sanding pour leftover paint down the drain or in water courses. In the event of spills, contain spillage using sand or earth soil. No added Lead, Mercury or Chromium compounds.

#### APPLICATIONS :-

BOND	IWP-1	IWP-03
	INTERIOR WALL PRIMER	INTERIOR EMULSION
TYPE	EMULSION BASE	EMULSION WATER REPELLENT
Color	WHITE Translucent	WHITE Translucent
FLASH POINT	None	None
Viscosity of supply at 30 oC		100-116 kerbs Units on stormer viscometer
Area of applications	Interior plasters, concrete, asbestos and cement sheets, bricks and stones.	Interior plasters, concrete, asbestos and cement sheets, bricks and stones.

<b>Thinner recommended</b>	40-100 % volume with water	50-70 % by volume with water
<b>METHOD OF USE</b>	Brush/Roller/pump spray/ Trigger spray/ sponge	Brush/Roller/pump spray/ Trigger spray/ sponge
<b>Stability of thinned paint</b>	Use with 24 hours	Use with 24 hours
<b>COVERGE / Lit./ coat</b> (Theoretically) <b>Approximate by brush</b>	10-12 Sq. meter / liter/ coat	25-30 sq. ft. per liter per coat
<b>Drying time at 30 oC &amp; 60-+5% R.H.</b>	30 minutes	Surface dry 20-30 minutes , full dry one week.
<b>Recoating Time</b>	Up to 24 hours after touch dry	Up to 24 hours after touch dry
<b>Finish</b>	Semi smooth	Smooth matt
<b>Water Repellency</b>	No	After 100 % drying Excellent
<b>Shade available</b>	No	As per shade card
<b>STORAGE LIFE Months</b>	12 months	12 months
<b>PACKING LITERS</b>	4, 10 & 20 liter in plastics buckets.	4, 10 & 20 liter in plastics buckets.

The information contain here in is reliable and accurate the best of our knowledge. Technical services will provided for guidance when required. However conditions of uses and methods of application are beyond our control, no warranty is expressed or implied.

ALSO AVAILABLE CONSTRUCTION CHEMICALS LIKE CEMENT ADDITIVES, WATERPROOFING COATINGS, WATER REPPALENTS, CHEMICALS & ABRASION RESISTANCE FLOORINGS MATERIALS, EPOXY-POLYURETHANE RESINS, GOUTING MATERIALS, ANTI CORROSIVE PAINTS, FACADE PAINTS, SEALENTS AND ADHESIVES, RETRO REINFORCING REHABILITATION MATERIALS. FOR BUILDING, BRIDGE, DAM, CANAL, TUNNEL AND MARINE STRUCTURES, ETC

#### **MR. BOND POLYCHEM**

111, Shivam Complex, Science city road, Sola, Ahmedabad-60 (Guj) India

mail: [jpbond009@yahoo.co.in](mailto:jpbond009@yahoo.co.in) / [info@mrbond.co.in](mailto:info@mrbond.co.in) / [contact@mrbond.co.in](mailto:contact@mrbond.co.in)

web: [www.mrbond.co.in](http://www.mrbond.co.in) / [www.mrbond.org](http://www.mrbond.org)

M-0 94094 57994 / 093279 24007 Ph: 079-2777 4269



BOND

BOND

