

---

**Typical chemical and physical properties**

**D'FOAM ACC 7025** is an organic defoamer especially formulated for the production of cement / asbestos roofing sheets.

**A Proprietary blend of polydimethylsiloxane , silicone Glycol and other surface Active components**

Properties:

Appearance	Milky White Thick Emulsion
Active content	> 30 %
Specific gravity at 25 °C	approx. 1.0

---

**Applications and typical treat level recommended**

Dosage

150 - 350ppm

**D'FOAM ACC 0353** can be diluted with water in a ratio of 1:5 to form a ready dispersion that can be added to the foaming media for quick control of foaming in the slurry tank

**D'FOAM ACC 0353** may also be distributed with a water dilution system and or with a special metering system for automatic dosing in the fermentation, which means product will automatically added only when needed.

---

**Benefits**

**D'FOAM ACC 0353** is a 30% active product and shows excellent performance in the control of foams and improves the flow and reduces viscosity of the medium.

It leaves no residues in the pipes or valves of the equipment used.

**Disclaimer:**

*All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

