

Typical chemical and physical Properties

D'FOAM ACC 62 is a defoamer in free-flowing powder form suited for applications such as dry mix adhesives, oil & gas exploration, gas-cut mud, plaster compositions, joint compounds, cement patchings, Putties and underlaying compositions.

PROPERTIES:

Appearance	Off-white powder
Active Content	65%
Dispersibility / Solubility	Dispersible in water
pH	8.5 ± 1.0
Bulk Density	0.40 to 0.60 g/ml

Applications and typical treat level recommended

D'FOAM ACC 62 can be easily added / blended into all components of dry mix formulations. Recommended level of addition is approx. 0.1% to 0.4% of total weight.

Benefits

D'FOAM ACC 62 is specially designed for those products that have been modified with polyvinyl acetate, polyvinyl alcohol, casein, soya protein, wheat flour, dextrin and similar materials.

Dry mixes containing **D'FOAM ACC 62** wet out faster and more uniformly. Air bubbles that cause problems in pumping, trowelling and obtaining a complete cavity fill, are not trapped in the wet mixture. It also prevents excessive shrinkage, porosity and weakness of set material.

D'FOAM ACC 62 acts as an ideal de-gassing additive in oil well drilling and gas-cut mud process.

Disclaimer:

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

D'FOAM ACC 62

Defoamer in Powder Form

Safety and Handling	Please read Material Safety Data Sheet (MSDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*