





# THE POWER OF BOND









### ZORRO™ BOND-WP

PROFESSIONAL GRADE MULTI-PURPOSE HIGH-PERFORMANCE SYNTHETIC RESIN FAST SETTING SUPERIOR WATER RESISTANT WHITE ADHESIVE

**ZORRO BOND-WP** is a synthetic resin adhesive in the form of milky white viscous paste ready to use & high-performance, high initial grip to form faster bonds with a strong grip, wood bonding solution in most challenging condition of water exposure, in high humidity areas.



### **FEATURES**

- · Ready to use
- · Unparalleled bonding strength
- · 48 hours continuous cold water resistance
- · One hour boiling water resistance
- · Superior bonding in marine plywood
- · Higher coverage
- · Quick setting
- · Non toxic & DBP free
- Non flammable
- · Eco-friendly & non-hazardous
- Prevents termite
- · Extreme (D3) bounding strength

### **PRECAUTIONS & LIMITATIONS**

- · Keep the container tightly closed when not in use.
- · Wash hands thoroughly after handling.
- · Store under ideal conditions in cool & dry place.

### **APPLICATION**

- For all type of wood both cold press & hot press, also ideal for bonding plywood, MDF & particle board with each other & also for bonding with laminate or veneer, as well as for finger jointing & wooden flooring.
- All round solution for wood bonding applications under the most challenging condition of water exposure. Kitchen units, wall units, bathroom where exposure to water is high.
- For sports goods, pencil, carpet manufacturing etc.
- Recommended for bonding any two material where at least one of them is porous e.g. card board, paper, particle board etc.

### PACKING

- · In plastic containers 500gm,1kg, 2kg
- Bucket 5kg,10kg, 20kg
- · Carboy 30kg, 50kg
- · Carboy (P) 50kg

### **HOW TO APPLY**

- · Clean both the surfaces to be bonded.
- Stir the container well before the application with a brush, roller, spreader or fingers.
- Apply a thin coat of ZORRO BOND–WP on both or one surface (as per requirement).
- Press the two surfaces together and keep under pressure till the adhesive dries completely.
- Excess adhesive pressed outside the joints should be wiped out with a wet cloth.



ZORRO\* BOND-XP

PROFESSIONAL GRADE MULTI-PURPOSE HIGH-PERFORMANCE SYNTHETIC RESIN FAST SETTING WHITE ADHESIVE

**ZORRO BOND-XP** is a synthetic resin adhesive in the form of milky white viscous paste ready to use & high-performance with high water resistance and very fast setting time. It is pva based with a high solid content to provide high strength. Its special formulation provides very lasting bonds on all types of wood and laminates.



## ZORRO\* BOND

PROFESSIONAL GRADE ECONOMICAL MULTI-PURPOSE SYNTHETIC RESIN WHITE ADHESIVE

**ZORRO BOND** is a white viscous professional grade multi purpose synthetic resin white adhesive for wood working and general bonding applications, economical, better coverage and fast drying adhesive.



### **FEATURES**

- Economical
- · Ideal for furniture manufacturer
- Ready to use
- Higher coverage
- · Fast drying

### **PRECAUTIONS & LIMITATIONS**

- · Keep the container tightly closed when not in use.
- · Wash hands thoroughly after handling.
- Store under ideal conditions in cool & dry place.

### APPLICATION

- · Join wood to wood.
- · Join ply to wood.
- · Join decorative laminates
- · Bonding soft and hard wood species.
- · Bonding particle board etc.

#### PACKING

- · In plastic containers 250gm, 500gm, 1kg, 2kg
- · Bucket 5kg, 10kg, 20kg
- · Carton 20Kg
- · Carboy 50kg
- · Carboy (P) 50kg

### **HOW TO APPLY**

- Clean both the surfaces to be bonded.
- Stir the container well before the application with a brush, roller, spreader or fingers.
- Apply a thin coat of ZORRO BOND on both or one surface (as per requirement).
- Press the two surfaces together and keep under pressure till the adhesive dries completely.
- Excess adhesive pressed outside the joints should be wiped out with a wet cloth.



# ZORRO™ BOND-HR‡

PROFESSIONAL GRADE MULTI-PURPOSE HIGH-PERFORMANCE SYNTHETIC RESIN FAST SETTING WHITE ADHESIVE

**ZORRO BOND-HR**‡ is a synthetic rubber adhesive in the form of a clear viscous paste used for fixing of furniture, foams, carpets, upholstery and footwear. The product has a very high strength, high heat resistance capacity upto 180° celsius and is very useful in bonding verticle and curved surfaces quickly.



### **FEATURES**

- Ready to use
- High coverage
- · Quick setting
- Fact drying

### **APPLICATION**

- · Vertical laminations on high walls
- Curved surface laminations
- ZORRO BOND-HR‡ is highly recommended for incide lamination of cabinate & storages as

### **HOW TO APPLY**

- · Clean both the surfaces to be bonded.
- Stir the container well before the application with a brush, roller, spreader or fingers.
- Annly a thin coat of ZORRO ROND-HRt or

PROFESSIONAL GRADE MULTI-PURPOSE HIGH-PERFORMANCE SYNTHETIC RESIN FAST SETTING WHITE ADHESIVE

ZORRO BOND- PVC is a white viscous professional grade multipurpose synthetic resin white adhesive for fixing of new age materials like acrylic and pvc sheets. The product is highly recommended for mutual binding, high initial grip to form faster bonds with a strong grip, excellent spread availability, high coverage & excellent to heat prone applications such as kitchen or high temperature climate zones.



### **FEATURES**

- Ready to use
- High coverage
- Quick setting
- Fast drying
- Unparalleled bonding strength
- Excellent compatibility with PVC and acrylic
- Used for manual edge binding
- Excellent heat resistance
- **Excellent spreadability**

### **PRECAUTIONS & LIMITATIONS**

- Keep the container tightly closed when not in use.
- · Wash hands thoroughly after handling.
- · Store under ideal conditions in cool and dry place.

### **APPLICATION**

- Fixing plywood to PVC sheets/rolls
- Fixing plywood to acrylic sheets
- PVC edge binding
- Fixing ply board to charcoal sheets

### **PACKING**

- · In plastic containers 1kg
- · Bucket 5kg

### **HOW TO APPLY**

- Clean both the surface to be bonded.
- Stir the container well before the application with a brush, roller, spreader or fingers.
- Apply a thin coat of ZORRO BOND-PVC on both or on surface (as per requirement.)
- · Press the two surfaces together and keep under pressure till the adhesive dries completely.
- Excess adhesive pressed outside the joints should be wiped out with a wet cloth.



### AIPL initiates to bring in a change

AIPL recently joined hands with Phenk Mat, an initiative that discourages vehicle owners from littering the roads by distributing disposable bags to be carried





### AIPL MARKETING PVT. LTD.

302, 3rd Floor, D-Mall, Netaji Subhash Place, Opp. Wazirpur DTC Depot, Delhi-34 For Consumer Complaint Please Contact Customer Care: 011-49010144, Mob.: +91-8448892000, 9555222772, E-Mail: info@aiplabro.com



