

ZORROCRETE | 2K011

Waterproofing & Repair Product



2K011 ZORROCRETE

Waterproofing & Repair Product

TWO COMPONENT READY TO USE ACRYLIC BASED WATERPROOF COATING SYSTEM.

AREAS OF APPLICATION

- Water tanks
- Terraces
- Sunshades
- Retaining walls
- Swimming pools etc
- Roofslabs
- Balconies
- Sunken toilets
- Basements

FEATURES AND BENEFITS

- Elastomeric Coating with 40-50% elongation.
- DFT.1 mm, four times thicker than ordinary polymer cement coating.
- Factory controlled & pre-packed, consistent in quality.
- Easy to apply by brush or in thin trowel applications.
- Protects concrete against water penetration, chloride and carbonation.
- Waterproof for concrete structure.
- Flexible, bridges hairline cracks in concrete & plaster.
- Non-toxic, good for potable water tanks.
- Prebatched, no additional cement, sand and water required to make the slurry

COVERAGE

Approximately 6-7 sq.ft/per kg of mixed material in two coats with a thickness of 1 to 1.2 mm depending on the surface undulations.

PACKAGING

3kg & 15 kg

SHELF LIFE & STORAGE

Shelf life is 12 months from the date of manufacturing. Store under cover, away from direct sunlight and protect from extreme temperature. In hot temperature conditions, it must be stored in a temperature-controlled environment i.e. less than 30c.



ZORROFIX TILE GROUT | 012TG

Ready to use waterproof coloured tile joint filler



012TG ZORROFIX TILE GROUT

Ready to use waterproof coloured tile joint filler

POLYMER MODIFIED CEMENTITIOUS GROUT FOR WALL AND FLOOR TILE JOINT.

ZORROFIX TILE GROUT 012TG is a gap filling material between different wall and floor tiles like ceramic, glazed, vitrified, mosaic, glass mosaic and marble tiles etc.

It effectively fills the gaps and levels itself to give hard wearing, non-dusting tile joints. ZORROFIX TILE GROUT 012 TG does not allow moisture and water to seep into the back of the tiles that causes dislocation. It holds the tiles firmly together to give them a long life.

FEATURES AND BENEFITS

- Cementitious, only water to be added.
- Excellent bond with tiles.
- Non Shrinking-Occupies the filled space permanently without shrinking
- Waterproof
- Polymer based
- Easy to use and clean
- Non-dusting

COVERAGE

Depends on tile size & joint width.

PACKAGING

1 kg.

SHELF LIFE & STORAGE

1 year if stored in its original pack.



ZORROCLEAN | 013TC

Multipurpose Stain Remover



013TC ZORROCLEAN

Multipurpose Stain Remover

HIGH QUALITY DETERGENT BASED CLEANING AND DEGREASING SOLUTION FOR MOSAIC, CERAMIC, GLAZED TILES, BATHTUBS, WASHBASIN, PRIVY BASIN AND CONCRETE.

ZORROCLEAN 013TC is a powerful but gently concentrated detergent based (mildly acidic) tile cleaner for tiles, wash basin, bath tubs, privy basin and concrete etc. Rapid removal of white yellowish spot/layer along with water stains over tiles, cement stains, grime, oil, grease, paint stains, moss and wax from concrete asbestos & ceramics.

Its unique formula is ideal for residential and commercial use.

FEATURES AND BENEFITS

- Removes the most stubborn stains easily.
- Does not damage joint between ceramic tiles, even those grouted with coloured products.
- Fast acting
- Does not effect glaze of tiles.
- Excellent tolerance to hard water.

COVERAGE

4 to 6 m²/ ltr dependent upon porosity & contamination of substrate.

PACKAGING

500 ml & 1 ltrs

SHELF LIFE & STORAGE

24 months if unopened.
Store in damp proof covered shed/godown.



ZORRO NEW SOLO COAT | 014NC

3-COAT WATERPROOF COATING FOR TERRACES



014NC ZORRO NEW SOLO COAT

3-COAT WATERPROOF COATING FOR TERRACES

HEAVY DUTY DURABLE REINFORCED ACRYLIC WATERPROOF COATING FOR TERRACE

Is a heavy-duty; microfibre reinforced acrylic based flexible terrace waterproof coating. ZORRO NEW SOLO COAT 014 NC is a three-coat system ensuring proper buildup of the thickness, making it a reliable waterproofing system.

FEATURES & BENEFITS

- Better film thickness - Provides 1mm to 1.25mm dry film thickness in 3 coats.
- High Crack bridging ability - Bridges cracks upto 2 mm width.
- No need to remove existing sound BB coba, Plaster, concrete surface.
- Can be used for flat as well as sloping roofs.
- High tensile strength, tear resistance & bond strength - With cementitious substrates as compared to available products.
- No streeting required for normal foot traffic.
- Good resistance - Against UV, Infrared rays and algal & fungal growth Light in weight.
- Easy in application - Can be applied by roller.
- Non toxic, breathable & washable.
- Aesthetic finish - Available in White colour.
- Surface to be primed with ZORROFIX Primer before application of coating.

AREA OF APPLICATION

- All new RCC flat and sloping roofs.
- Existing cementitious waterproofing treatments like brick-bat-coba, concrete screeds, acrylic coatings, etc.

PACKING

5 Kg & 20 Kg

COVERAGE

*1.80 to 2.00 m² per kg per coat. (Coverage may vary depending upon condition of the surface)

SHELF LIFE & STORAGE

Shelf life is 24 month from the date of manufacturing in unopened condition. Store in cool & dry place.



CONSTRUCTION CHEMICALS FOR WATERPROOFING & REPAIR

NEW PRODUCTS



AIPL MARKETING PVT. LTD.
409, 4th Floor, D-Mall, Netaji Subhash Place,
Opp. Wazirpur DTC Depot, Delhi-110034
For Consumer Complaint Please Contact : 011- 49010190
Mob: +91 8595167806. Email: info@aiplzorro.com
www.aiplzorro.com

TOLL-FREE NO
1800-27-40409

ZORROPROOF | 007L

Liquid Waterproofing Product



007L

ZORROPROOF
Liquid Waterproofing Product

Liquid integral waterproofing compound for concrete and mortar.

AREAS OF APPLICATION

Water reducing and waterproofing admixture for all types of concrete and mortar. It is used for waterproofing of concrete and sand cement mortar used in basements, roof slabs, screeds, water retaining structures, beams, columns, culverts, tunnels, sunken slabs, terrace slabs, water tanks, sewerage works etc.

FEATURES AND BENEFITS

- Being a liquid it is easily dispersible & compatible with concrete/mortar mixes.
- Increases workability of the concrete mix without increased water content.
- Compatible with all varieties of Portland cement including Slag Cement.
- To be added to gauging water before adding to the mix required at a very small dosage hence convenient to handle and greater economy.
- Increases cohesive property of concrete / mortars thus eliminating segregation and bleeding.
- Minimises porosity & capillary action.
- Rebound loss is low.
- It reduces the permeability of water into concrete.
- Reduces shrinkage crack development in concrete and plasters.
- No added chloride.

PACKAGING

ZORROPROOF007L is available in 200 ml, 1 ltr, 5 ltr, 10 ltr, 20 ltr, 50ltr & 200 ltr.

SHELF LIFE & STORAGE

Shelf life 24 months from the date of manufacturing.
Store in a cool dry place in unopened condition.
(Prevent from direct sunlight)



DOSAGE

200ml for 50kg bag of Cement.

ZORROCRETE | 008W

Waterproofing & Repair Product



008W

ZORROCRETE
Waterproofing & Repair Product

ZORROCRETE 008W is Styrene Butadiene Rubber based bonding agent.

AREAS OF APPLICATION

- For waterproofing of Roof Slabs, Sunken Slabs, Basements, Water Tanks, Balconies, Sunshades etc.
- It is used as a Bonding Agent between old & new concrete for cementitious substrates.
- It is also effective to make repair mortars & concrete in building rehab work.
- Treatment for leaching & salt petre action.
- It is multipurpose mortar admixture for injection grouts.

FEATURES AND BENEFITS

- White turbid liquid can be easily applied by brush.
- Provides excellent bond to concrete, adhesion plaster, masonry, stone work, etc.
- Strengthening cold joints between old and new concrete and making them non-permeable.
- Multi-purpose use as a bonding agent, modifier for cement-sand & concrete mixes in building repairs.
- Gives weather resistant mortar with improved durability impermeability to chlorides and other harmful agents.
- Excellent as a cement modifier.
- It prevents cracking by improving flexural strength.
- Allows breathing thus preventing peeling off.
- Repair mortar modified with LATEX ZORROCRETE WRP is suitable for repairing of RCC beams, columns, slabs and other RCC members.
- Reduces shrinkage & water permeability in concrete & mortar.
- Good as a bonding agent in repairs & renovations.
- Reduces chloride/salt penetration in marine environment.
- Compatible with all common hydraulic cements.



TO KNOW MORE
CALL ZORRO
EXPERT

08595167806

COVERAGE/DOSAGE

		COVERAGE*
AS A PASSIVATOR COAT	1:1 (Zorrocrete 008W: Cement)	2-3 Rmtr/ kg for 25 mm dia bar at 1 mm thickness
AS A WATERPROOF COATING	1:1.5 (Zorrocrete 008W : Cement)	1.5 - 2 m ² / kg for 2 coat at 0.5-0.6 mm thickness
AS BONDING COAT	1:1 (Zorrocrete 008W : Cement)	2-3 m ² / kg

PACKAGING

500 gm, 1 kg, 5 kg, 10 kg, 20 kg, 50kg & 200kg

SHELF LIFE & STORAGE

Shelf life 18 months from the date of manufacturing.
Store in a cool dry place in unopened condition.
(Prevent from direct sunlight)



ZORROCRACKFIX | 009C

Crack Filler



009C

ZORROCRACKFIX
Crack Filler

READY TO USE PASTE FILL CRACKS FOR INTERNAL & EXTERNAL SURFACES IN PLASTER

ZORROCRACKFIX 009C is high quality weather durable acrylic based ready to use flexible putty which is easy to use for filling cracks in plastered surfaces because it has excellent bonding, ease of application, durability, water resistance & aesthetic

AREAS OF APPLICATION

- Repairing of internal and external cracks in plastered surfaces up to 5 mm X 5 mm size.
- Suitable for both vertical and horizontal applications wherever hairline cracks are observed.
- It can be used for leveling the undulations of the un-plastered or plastered ceilings & walls before painting.

FEATURES AND BENEFITS

- Easy to apply by putty knife similar to conventional putties.
- Accommodates slight movements in the cracks.
- No Shrinkage Non staining. Single component.
- For both internal and external surfaces.
- Over-coatable by any type of water based paints after 24 hours.
- For cracks in cement plaster upto 5 mm wide.
- UV and water resistant.
- It can be used as putty on plastered surfaces in patch works.
- It can be tinted using water based stainers.
- Excellent adhesion.
- Can be applied on damp surfaces but not on cracks with running water.

COVERAGE

Approx. 25 RMT/kg for 5 mm X 5 mm crack depending on site conditions.

PACKAGING

500gm, 1kg & 5kg

SHELF LIFE & STORAGE

24 months from the date of manufacturing in unopened containers.
Away from moisture and heat.



ZORROCRETE | 010AP

Waterproofing & Repair Product



010AP

ZORROCRETE
Waterproofing & Repair Product

ACRYLIC MIDIFIER

ZORROCRETE 010AP is a single component 100% acrylic co-polymer admixture specially developed to improve the properties of cementitious compositions

AREAS OF APPLICATION

- Waterproofing of terrace, toilets, chajja, masonry walls, sloping RCC roofs, etc.
- For making polymer mortar for repairs mortars etc.
- As a bonding agent on cold/construction joints.
- Multipurpose mortar admixture for injection grouts.
- Treatment of leaching & salt pester action.
- Additive to cement based paints for waterproofing.

FEATURES AND BENEFITS

- Good bonding properties
- Good as a waterproof coating
- Static cracks can be filled with mortar made with ZORROCRETE 010AP
- A good modifier to make repair mortar/concrete
- Durable to UV exposure
- Eco-friendly

COVERAGE

15-20 sq.ft/1tr for 2 coats.(ZORROCRETE 010AP+Cement in the proportion 1:2)

PACKAGING

500 ml, 1ltr, 5 ltr, 20 ltr, 50 ltr & 200 ltr.

SHELF LIFE & STORAGE

Shelf life 24 months from the date of manufacturing .Store in a cool dry place in unopened condition.
(Prevent from direct sunlight)

