

PORTABLE CNC PROFILE CUTTING MACHINE

Oxy-Fuel type



Features

- Easy to use
- Portable & light weight
- Wider strong frame
- Kerf compensation
- Built-in library of standard shapes
- 64M memory for users' program

Specifications

Working Area (cutting area)	mm	3000x 1500 (l x w) standard Customized with width 1.5 ~ 1.8m, length 3m, 4m, 5m.....15m max
Cutting Thickness	mm	5 to 150 (MS material)
Cutting Speed (profiling speed)	mm/min	0 to 600mm/min (variable, depends on thickness)
Track Type		Rack and Pinion
X / Y Guide Ways		Precision LMG / Linear Shafts
Drive Systems (axis movement)	standard	Hybrid Stepper Motors with Micro Stepping Drives
Z-Axis Travel	standard	150mm (up to 300mm optional)
Torch Height Controller		Yes – capacitive type
Plasma Upgradable		Yes
CNC Controller : Model F2100B		7 inch high resolution color LCD screen
Power Input		215V/50Hz/1Ph AC for controller

Standard Accessories: Cutting Torch | Sets of Nozzles (3 nos) | Operation Manual

ARSUN ENGINEERS

56/1 Vithalwadi Industrial Estate

Bhavnagar 364001, INDIA

Phone: 0278-2514076 | Fax: +91-278-2514077

Email: sales@arsun.com

www.arsun.com