



Chill with Elan

Professional Cooling By Cool Professional

Hospitality Solutions - Kitchen Refrigeration - Static Cooling



Reach in RI 550 C/RI 550 F



Reach in RI 1100 C/RI 1100 F



Combi Reach in RI 1100 CF

Key Features:

- ▶ Tropicalized to perform at 43°C ambient
- ▶ DANFOSS/EMBRACO compressor
- ▶ Dixell/Eliwell digital controller
- ▶ EBM Fan Motor
- ▶ SS 304 food grade steel interior
- ▶ Static cooling with fan for uniform cooling
- ▶ Removable gasket
- ▶ Adjustable shelves
- ▶ Heavy duty castor for Reach in & Under counter
- ▶ Lock in Reach in & Under counter
- ▶ Built in handle
- ▶ Environment Friendly Refrigerant
 - ▶ R134A for chillers
 - ▶ R404A for freezers



Under Counter UC 1500 C/UC 1500 F



Under Counter UC 1800 C/UC 1800 F

Model	Description	Capacity (Ltrs)	Dimension (W x D x H Inch)	Temperature Range	No. of Shelves
RI 550 C	2 Door Reach In Chiller	550	25 x 30 x 77	-2°C ~ 10°C	3
RI 1100 C	4 Door Reach In Chiller	1100	48 x 30 x 77	-2°C ~ 10°C	6
RI 550 F	2 Door Reach In Freezer	550	25 x 30 x 77	-10°C ~ -20°C	3
RI 1100 F	4 Door Reach In Freezer	1100	48 x 30 x 77	-10°C ~ -20°C	6
RI 1100 CF	Combi Reach In Freezer & Chiller	1100	48 x 30 x 77	-2°C ~ 10°C / -10°C ~ -20°C	6
EGN 600 Fish [®]	Reach In Fish Chiller	600	27 x 33 x 79	-2°C ~ 8°C	3
UC 1500 C	2 Door Undercounter Chiller	265	54 x 28 x 34	-2°C ~ 10°C	2
UC 1800 C	3 Door Undercounter Chiller	400	71 x 28 x 34	-2°C ~ 10°C	3
UC 1500 F	2 Door Undercounter Freezer	265	54 x 28 x 34	-10°C ~ -20°C	2
UC 1800 F	3 Door Undercounter Freezer	400	71 x 28 x 34	-10°C ~ -20°C	3

Specifications, features and colours are subject to change without any notice, due to continuous product development.

[®]Static Cooling [®]38°C Ambient

Hospitality Solutions - Kitchen Refrigeration - Frost Free



EGN 600 C2 / EGN 600 F2
EGN 650 C2 / EGN 650 F2

Gastronorm Reach Ins

Elanpro Professional Reach Ins for refrigerating or freezing are designed to meet the tough Indian Kitchen Conditions. Our machines are tested to perform in ambient environment of 43°C and presents a host of exciting new features.

Key Features:

- ▶ Tropicalized to perform at 43°C Ambient
- ▶ DANFOSS/EMBRACO Compressor
- ▶ Dixell Controller
- ▶ EBM Fan Motor
- ▶ SS 304 Food Grade Steel
- ▶ Castors
- ▶ Lock
- ▶ Ventilated Cooling
- ▶ Environment Friendly Refrigerant
 - ▶ R134A for Chillers
 - ▶ R404A for Freezers

Optional Features:

Reach In


- ▶ Left or Right Hinged Door
- ▶ Single or Multi Door

Undercounter

- ▶ Door/Drawer Option in 1x3, 2x3, 3x3 GN
- ▶ Back/Side Splash Guard
- ▶ Compressor on left or right side

Common - All Models

- ▶ HACCP Compliance
- ▶ Adjustable Feet



EGN 2100 C / EGN 2100 F



EGN 1200 C4 / EGN 1200 F4
EGN 1410 C4 / EGN 1410 F4

Elanpro Under counter

The Under counters come with a various counter top and door/drawer options thereby enhancing convenience and saving time & space that helps kitchen professionals to work more effectively.



EGN 3100 C / EGN 3100 F

Model	Description	Capacity (Ltrs)	Dimension (WxDxH)	Temperature Range	GN Compatibility	No. of Shelves
EGN 600 C2	2 Door Reach In Chiller	600	27 x 32 x 79	-2°C ~ 10°C	2 x GN 1/1	3
EGN 1200 C4	4 Door Reach In Chiller	1200	53 x 32 x 79	-2°C ~ 10°C	2 x GN 1/1	6
EGN 600 F2	2 Door Reach In Freezer	600	27 x 32 x 79	-16°C ~ -22°C	2 x GN 1/1	3
EGN 1200 F4	4 Door Reach In Freezer	1200	53 x 32 x 79	-16°C ~ -22°C	2 x GN 1/1	6
EGN 600 CF	Combi Reach In Freezer & Chiller	600	27 x 31 x 79	-2°C ~ 10°C / -10°C ~ -20°C	2 x GN 1/1	3
EGN 650 C2	2 Door Reach In Chiller	650	29 x 33 x 79	-2°C ~ 10°C	2 x GN 1/1	3
EGN 1410 C4	4 Door Reach In Chiller	1410	58 x 33 x 79	-2°C ~ 10°C	2 x GN 1/1	6
EGN 650 F2	2 Door Reach In Freezer	650	29 x 33 x 79	-16°C ~ -22°C	2 x GN 1/1	3
EGN 1410 F4	4 Door Reach In Freezer	1410	58 x 33 x 79	-16°C ~ -22°C	2 x GN 1/1	6
EGN 2100 C	2 Door Undercounter Chiller	265	54 x 28 x 34	-2°C ~ 10°C	1 x GN 1/1	2
EGN 3100 C	3 Door Undercounter Chiller	400	71 x 28 x 34	-2°C ~ 10°C	1 x GN 1/1	3
EGN 2100 F	2 Door Undercounter Freezer	265	54 x 28 x 34	-16°C ~ -22°C	1 x GN 1/1	2
EGN 3100 F	3 Door Undercounter Freezer	400	71 x 28 x 34	-16°C ~ -22°C	1 x GN 1/1	3

Manufactured as per European Technology and Standards

GN Pan are optional

Hospitality Solutions - Salad & Prep Counters



Salad Under Counter ES 900

Also available in 3 doors

Key Features:

- Easy to clean 304 grade stainless steel interior and exterior
- A unique, hinged night cover in pure stainless steel for food safety
- Static cooling models are with fan for uniform cooling
- Self closing door
- Removable gasket
- Digital temperature display




EVRX 1200



Frost Top 3F

ES 900



ES 903



EPS 200

Also available in 3 doors



ESH 3000

Also available in 2 doors

Model	Description	Capacity (Ltrs)	Dimension (W x D x H Inch)	Temperature Range	No. of Shelves/Pans
ES 900	2 Door Salad Under Counter / Solid Top	240	36 x 28 x 34	2°C ~ 10°C	2
ES 903	3 Door Salad Under Counter / Solid Top	360	54 x 28 x 34	2°C ~ 8°C	3
EPS 200	2 Door Under Counter with Prep Table	240	36 x 28 x 38	2°C ~ 8°C	5 x GN 1/6
EPS 300	3 Door Under Counter with Prep Table	360	54 x 28 x 38	2°C ~ 8°C	8 x GN 1/6
ESH 2000	2 Door Under Counter with Prep Table	337	60 x 32 x 42	2°C ~ 8°C	6 x GN 1/3
ESH 3000	3 Door Under Counter with Prep Table	497	80 x 32 x 42	2°C ~ 8°C	10 x GN 1/3
Frost Top 3F	Frost Top	NA	44 x 27 x 17	-10°C	NA
EVRX 1200	Display Counter	NA	48 x 13 x 17	2°C ~ 8°C	5xGN 1/4
EVRX 1400	Display Counter	NA	56 x 13 x 17	2°C ~ 8°C	6xGN 1/4

GN Pans are not provided.

Specifications, features and colours are subject to change without any notice, due to continuous product development.

All units suitable to work at ambient 38°C

Blast Chillers & Freezers



D3



D5

Key Features:

- CFC refrigerant and foam
- Complete structure interior & exterior in stainless steel with round internal edges for easy cleaning
- Self closing doors with easy to clean and replace magnetic balloon gasket
- Electric door mullion heater replaceable
- 75mm thickness insulation for excellent thermal efficiency
- Ventilated refrigeration compartment
- Dixell controller and compact footprints optional
- Danfoss refrigeration components
- Aspera or Danfoss compressor
- EBM Fan



Blast Chillers 70°C to 3°C

The Blast Chilling cycle, the product temperature drops from 70°C to 3°C in 90 minutes.

The transition between 65°C and 10°C (ideal climate for the proliferation of bacterial), so fast as to prevent any generation.

The Foodstuff can be kept for 8 days in normal Chiller.



Shock Freezers 70°C to -18°C

The maximum storages is achieved through the rapid production of cold to allow the production of micro crystals that optimally preserve the cells of the foodstuff.

The Shock Freezing drops the temperature from 70°C to -18°C in a maximum time of 240 minutes.

The food is quickly frozen and then be kept for months in normal freezer.

Model	Dimension (W x D x H Inch)	Capacity (Ltrs)	Cooling Capability*	Tray	Power Supply	Cooling Mode
T3	24 x 23 x 15	39	8 kg / 5 kg	3	230 V / 50 Hz	Ventilated
D3	31 x 32 x 37	139	12 kg / 8 kg	3	230 V / 50 Hz	Ventilated
D5	31 x 32 x 40	169	18 kg / 14 kg	5	230 V / 50 Hz	Ventilated
D10	31 x 32 x 65	368	40 kg / 28 kg	10	230 V / 50 Hz	Ventilated
D14	31 x 32 x 85	494	55 kg / 38 kg	14	380 V / 50 Hz	Ventilated

Specifications, features and colours are subject to change without any notice, due to continuous product development.

* 70/3°C in 90 minute & 70/-18°C in 240 minute.

Confectionery Showcases



EDC 300 C/EDC 450 C



EDC 300 F/EDC 450 F

Available in
Hot, Ambient
and Grab & Go
Options

Key Features:

- DGU glass for best insulation & better visibility.
- Imported front DGU glass.
- Stainless steel interior.
- LED lights on each shelf
- Removable Condensing unit for easy servicing.
- Ventilated refrigeration.
- Anti - mist system on front & back.
- Front glass openable in curved model for cleaning purpose.
- Front & Back heated glass
- Colour : Black & Cream

Key Features:

- ▶ CFC Free
- ▶ Ventilated refrigeration compartment
- ▶ Auto defrosting
- ▶ Electronic thermostat and digital LED temperature display
- ▶ Rear sliding door
- ▶ Fan forced airflow
- ▶ Chrome wire shelves



HTR 160 Cold



HTH 160 Hot



LSC 408

Model	Description	Dimension (W x D x H Inch)	Temperature Range	No. of Shelves/Pans
HTH 160	Countertop Hot Showcase	34 x 23 x 27	30°C ~ 90°C	Base + 2
HTR 160	Countertop Cold Showcase	34 x 23 x 27	2°C ~ 8°C	Base + 2
LSC 408	4 Side Pastry Showcase	28 x 28 x 71	2°C ~ 8°C	Base + 4
EDC 300 C	Pastry Showcase	37 x 27 x 47	2°C ~ 8°C	Base + 3
EDC 300 F	Pastry Showcase	37 x 27 x 47	2°C ~ 8°C	Base + 3
EDC 450 C	Pastry Showcase	53 x 27 x 47	2°C ~ 8°C	Base + 3
EDC 450 F	Pastry Showcase	53 x 27 x 47	2°C ~ 8°C	Base + 3

Specifications, features and colours are subject to change without any notice, due to continuous product development.

30°C ambient temperature / 65% RH

Ice Machines/Flakers



EIM 31 / EFM 101



EIM 61



EIM 101



EIM 61 BW



Dice

Key Features:

- Air cooled
- Control board with display
- Option of flake & dice shape
- Option of vertical & horizontal evaporator
- Stainless steel or colour steel
- Adjustable feet



EIM 201 / EIM 351 / EIM 501



EIM 1001

Model	EFM 101	EIM 31	EIM 61 / 61 BW	EIM 101	EIM 201	EIM 351	EIM 501	EIM 1001
Capacity* (Kg/24 hrs)	100	26	55	95	191	318	455	909
Bin Size (Kg)	20	11	18	40	105	125	125	315
Machine Dim. (WxDxH) inch	21 x 22 x 38	17 x 18 x 31	23 x 20 x 31	27 x 26 x 37	22 x 32 x 66	30 x 33 x 66	30 x 33 x 66	48 x 25 x 72
Ice Type	Flake	Dice	Dice	Dice	Dice	Dice	Dice	Dice
Cube Size (WxDxH) mm	NA	22 x 22 x 22	28 x 32 x 22	28 x 32 x 22	28 x 28 x 22	28 x 28 x 22	28 x 28 x 22	28 x 28 x 22

* Rated capacity at 10°C Water and 21°C Air.

Hospitality Solutions - Bar Refrigeration



EBB 20



EWG 50 D



EBB 30



EGN 2100 CG



EGN 3100 CG



GFSG



EWG 130 D



Key Features - Wine Chillers

- ▶ Two separate zones for Red and White wine
- ▶ Actual and set temperature display
- ▶ Lock
- ▶ No frost
- ▶ Anti-Vibration
- ▶ Elegant stainless steel door frame
- ▶ Double layer anti UV tinted glass door
- ▶ Cabinet colour: Black
- ▶ Pullout sliding shelves
- ▶ Wooden shelves

Particulars	GFSG	EBB 20	EBB 30	EGN 2100 CG	EGN 3100 CG	EWG 50 D	EWG 130 D
Descriptions	1 Door Glass Froster	2 Door Back Bar	3 Door Back Bar	Under Counter Bar	Under Counter Bar	Wine Cooler	Wine Cooler
Dimension (WxDxH)	24 x 20 x 34	35 x 21 x 35	54 x 21 x 35	54 x 28 x 34	71 x 28 x 34	24 x 24 x 34	24 x 27 x 64
Capacity	100 Ltrs.	223 Ltrs.	335 Ltrs.	265 Ltrs.	400 Ltrs.	42 Bottles	128 Bottles
Power Consumption (Watt)	280	230	320	396	514	113	175
Temperature Range	-10°C ~ -21°C	2°C ~ 10°C	2°C ~ 10°C	2°C ~ 10°C	2°C ~ 10°C	5°C ~ 12°C 12°C ~ 22°C	5°C ~ 12°C 12°C ~ 22°C
No of Shelf	2	2	3	2	3	6	11

Wide Range of Beer & Beverage Cooling Solution



Old Brewery (4-8)



IPRD 2



Sexy



Flute



Lucky



Shield



GT Touch 2

Model	Dimension (WxDxH)	Nos. of Bowls	Power in Watts	Tank Capacity
IPRD 2	16 x 23 x 34	2	980 W	11+11 Ltrs.
GT Touch 2	18 x 17 x 26	2	756 W	6+6 Ltrs.

*available in 1 or 3 Bowls options.



Super Flat Glycol



HE 250



HE 90 / 120

Cooling unit to dispense extra cold beer between 0°C & 2°C and to frost the tower

Model	Dimension (WxDxH)	Compressor	Tank Capacity	No. of Coils/Length	Ice Bank Kgs	Rate of Drink Per/Min (200 ml)	Cooling Capacity*
Mini Lady	16 x 16 x 12	1/6 Hp	12 H ² O/Ltrs.	1-2/8 Mtrs.	4	2 Glass	25 Ltrs./Hr.
HE 90	15 x 15 x 28	1/3 Hp	36 H ² O/Ltrs.	1-4/17 Mtrs.	14	8 Glass	90 Ltrs./Hr.
HE 120	18 x 18 x 31	1/2 Hp	50 H ² O/Ltrs.	1-8/22 Mtrs.	25	10 Glass	120 Ltrs./Hr.
HE 250	32 x 21 x 34	3/4 Hp	90 H ² O/Ltrs.	1-10/23 Mtrs.	40	20 Glass	250 Ltrs./Hr.

* Beer at 25°C input/4°C output in 25°C ambient

Model	Dimension (WxDxH)	Compressor	Power in Watts/ Kcal	Tank Capacity	Re-circulation Pump	Power Consumption
Super Flat Glycol	16 x 24 x 15	1/3 Hp	893 W/772 K	17 Ltrs.	18/20	500 W
Glycol HE 150	31 x 18 x 25	1/2 Hp	893 W/1264 K	60 Ltrs.	18/20	556 W



Mini Lady

Mini Bar & Mini Fridge



RB 40 G



RF 60 G



RB 40

Key Features-Minibar

- ▶ Ammonia refrigerant
- ▶ Very low energy consumption
- ▶ Silent operation
- ▶ Largest range to choose from
 - Sizes : 15 to 60 ltrs
 - Colour : Black, (Brown, & White) (MOQ 200 nos.)
 - Design : Regular, Deluxe & Glass

Key Features-Mini Fridge

- ▶ CFC free, R 134a refrigerant
- ▶ Low energy consumption and noise
- ▶ 60 ltrs. capacity available in elegant white colour
- ▶ Reversible door
- ▶ Lock (Optional)



RF 60



RB 40



RF 60

Model	RF 60*	RF 60 G**	RB 30	RB 40	RB 40 G	RB 60
Capacity Ltrs.	60	60	30	40	40	60
Input Power (W)	70	70	65	65	75	90
Energy Consumption	0.3	0.5	0.75	0.8	0.85	1.05
Temperature	2°C ~ 10°C		2°C ~ 10°C (at 28°C Ambient Condition)			
Product Dimension (WxDxH)	19 x 18 x 21	19 x 18 x 21	16 x 17 x 20	16 x 18 x 22	16 x 18 x 22	18 x 19 x 24
Container (20/40/40 HC)	230/460/573	230/460/573	240/500/620	206/460/484	206/460/484	132/264/352

Certifications CE/CB/UL

*at 38°C

**at 35°C

Retail Solutions - Special Products



ECG 85



ECG 60



ECG 25



RF 60 G



ECG 105



SD 50C / 90C



SC 42



SC 80

For more options and technical details, ask for detailed catalogue.

Product	Counter Top Cooler/Freezer/Can Coolers							
Model	SC 42	ECG 25	ECG 60	ECG 85	ECG 105	SD 50C	SD 90C	SC 80
Dim. (Inches)								
Width	24	12	17	19	19	23	24	NA
Depth	21	14	18	20	21	22	22	NA
Height	17	22	28	32	32	30	32	42
Diameter	NA	NA	NA	NA	NA	NA	NA	18
Capacity	40	25	60	85	105	50	90	80
Temperature range	12°C ~ 18°C	1°C ~ 8°C				-15°C ~ -18°C		1°C ~ 10°C
Ambient	35°C	35°C	35°C	35°C	35°C	27°C	27°C	32°C
No. of 330ml cans	NA	24	78	105	NA	NA	NA	84
Input Power Watts	NA	80	120	120	120	154	230	129

Electricals : 220V, 50Hz, Single phase specifications, features and colours are subject to change without any notice, due to continuous product development.

Retail Solutions

Showcases Freezers - from 60 ltrs. to 650 ltrs.



EKG 250 D / 310 D / 410 D / 625 D



EKG 150 D
(with optional Canopy)



EKG 650

New
Countertop
Cooler &
Freezer



EKG 60



Curve Glass (with optional Canopy)

Scooping
Canopy #



EKG 305 / EKG 405
(with optional Canopy)



PCF
110



EF 205 / EF 305

A+
Energy
Rating



EF 105



EF 405 (Combi)

Combi
Freezer &
Cooler



EF 600 DLX

New Blast
Chilling
Temp upto
-30°C



EF 455 / EF 555

DESCRIPTION	EKG 150 D	EKG 250 D	EKG 310 D	EKG 410 D	EKG 625 D	EKG 60	EKG 105	EKG 205	EKG 305	EKG 405	EKG 650
Type	Curve Glass Top Freezer					Flat Glass Top Freezer					
Capacity (Litres)	150	250	310	410	625	60	100	205	305	450	650
External Dim.- (Inches)											
Width	23	32	39	48	71	25	22	35	42	54	71
Depth	28	27	27	27	27	20	22	22	24	26	27
Height	34	34	34	34	36	20	33	33	33	33	33
Baskets / Shelves Qty.	3	3	4	6	9	1	2	3	4	4	9
No. of Door/Type	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass	2/Glass
Temperature range - °C	-16°C ~ -24°C										
Castors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes

* Under standard test conditions # Optional

Presenting Chest Freezers and Chillers with Dual Temperature

The exciting range of Chest Freezers / Chillers to meet your requirements from 100 ltrs. to 650 ltrs.

DESCRIPTION	EF 105	EF 205	EF 305	EF 455	EF 555	EF 600 DLX	EF 405 (Combi)	PCF 110	PCF 200
Type	Hard Top Chest Freezer cum Cooler							Push Cart Freezer	
Capacity (Litres)	100	200	300	410	520	650	225 F + 175 C	110	200
External Dim.- (Inches)									
Width	22	31	44	49	65	71	52	38	41
Depth	23	25	24	30	28	30	27	25	25
Height	33	32	33	36	33	34	39	28	34
Baskets / Shelves Qty.	2	2	2	2	2	1	2	NA	NA
No. of Door/Type	1/Solid	1/Solid	1/Solid	2/Solid	2/Solid	2/Solid	2/Solid	1/Solid	2/Solid
Temperature range - °C	8°C ~ -25°C							-18°C ~ -30°C	
Castors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	NA	NA
Lock	Yes	Yes	Yes	Yes	Yes	Yes	Yes	NA	NA

* Under Standard Test Conditions

Upright Showcase Chiller & Freezer (Frost Free & Static)



EDG 300 C
Grab & Go



ECG 305/ECG 405



ECG 205



ECG 625 DD



ECG 1100



EFGV 1000



EFGV 450



NSS 1800
Serve Over



EFG 401



EFGV 201



EIL 45



EIL 65



ABSS 220 - Multi Deck



EPM 100 / 150 - Multi Deck

DESCRIPTION	EFGV 201	EFG 401	EFGV 450	EFGV 1000	ECG 205	ECG 305	ECG 405	ECG 625 DD	ECG 1100	ABSS 220	EDG 300 C	EPM 100	EPM 150	EIL 45	EIL 65	NSS 1800
Type	Upright Freezer*				Upright Chiller					Grab & Go / Multi Deck*				Island Showcase		
Capacity (Litres)	200	400	450	950	200	300	400	625	1100	220	NA	600	800	399	660	1800
External Dim. (Inches)																
Width	19	24	27	54	20	21	26	36	54	24	37	42	62	63	67	74
Depth	28	23	28	28	24	21	23	28	28	18	27	29	29	28	36	38
Height	61	73	78	78	60	67	77	84	78	71	47	85	82	35	35	50
Baskets / Shelves Qty	3	7	5	10	3	4	4	3	10	3	Base + 3	4	4	4x2	4x3	NA
No. of Door/Type	1/Glass	1/Glass	1/Glass	2/Glass	1/Glass	1/Glass	1/Glass	2/Glass	2/Glass	NA	NA	NA	NA	2/Glass	2/Glass	1/Glass
Temperature range-°C	-16°C ~ -24°C				1°C ~ 10°C					2°C ~ 8°C				0°C ~ 10°C / -12°C ~ -23°C		
Castors	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	NA	NA	NA	NA	NA	Yes
Lock	No	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	NA	NA	NA	NA	NA	NA	Yes

Electricals : 220V, 50Hz, Single phase specifications, features and colours are subject to change without any notice, due to continuous product development.

* At 32°C ambient ** At 27°C ambient