

30mm x 25mm Cyclocross Full Carbon Clincher, Disc brake!

FSC30-CM-25 (30x25mm clincher, cyclocross)	
Rims:	30mmx25mm full carbon clincher for cyclocross 28H/28H (24H/24 & 32H/32H for option) No braking surface UD/3K, Matt/Glossy ERD: 584mm Weight: 430g/pc
Hubs for Option:	Novatec D711SB/D712SB , 407g/set Novatec D771SB./D772SB, 407g/set DT Swiss 240S (J-bend/Straight pull, Central Lock / 6 bolt) DT Swiss 350S Straight pull, central lock, 395g/set
O.L.D:	9mm*100mm, 10mm*135mm or 15mm*100mm, 12mm*142mm
Cassette Body:	Shimano 8/9/10/11s XX1, XD freehub is available Campagnolo 10/11s
Spokes for Option:	Sapim cx-ray spoke, Black (267g/set, 56pcs) Sapim cx-delta spoke, Black (267g/set, 56pcs)
Nipple:	Sapim Sils (Aluminium or Brass) Black or red. External or internal.
Lacing:	Standard: Standard: Front--3X, Rear non-drive side--3X, Rear drive side--3X Customized lacing is available
Other Specs:	Roundness: <0.2mm Offset: <0.2mm Max Tension: (Rim)300kgf, (Spoke); F:95kgf, R130kgf Max pressure(Clincher)145psi/10bar, (Tubular)125psi/8.6bar. Max Recommended Rider Weight: 95kgs

FSC88-CM-25 (88x25mm clincher, cyclocross)	
Rims:	88mmx25mm full carbon clincher for cyclocross 28H/28H (24H/24 & 32H/32H for option) No braking surface UD/3K, Matt/Glossy ERD: 472mm Weight: 700g/pc
Hubs for Option:	Novatec D711SB/D712SB , 407g/set Novatec D771SB./D772SB, 407g/set DT Swiss 240S (J-bend/Straight pull, Central Lock / 6 bolt) DT Swiss 350S Straight pull, central lock, 395g/set
O.L.D:	9mm*100mm, 10mm*135mm or 15mm*100mm, 12mm*142mm
Cassette Body:	Shimano 8/9/10/11s XX1, XD freehub is available Campagnolo 10/11s
Spokes for Option:	Sapim cx-ray spoke, Black (267g/set, 56pcs) Sapim cx-delta spoke, Black (267g/set, 56pcs)
Nipple:	Sapim Sils (Aluminium or Brass) Black or red. External or internal.
Lacing:	Standard: Standard: Front--3X, Rear non-drive side--3X, Rear drive side--3X Customized lacing is available

25mm Cyclocross Full Carbon Clincher

Other Specs:	Roundness: <0.2mm Offset: <0.2mm Max Tension: (Rim)300kgf, (Spoke); F:95kgf, R130kgf Max pressure(Clincher)145psi/10bar, (Tubular)125psi/8.6bar. Max Recommended Rider Weight: 110kgs
---------------------	---

FSC50-CM-25 (50x25mm clincher, cyclocross)

Rims:	50mmx25mm full carbon clincher for cyclocross 28H/28H (24H/24 & 32H/32H for option) No braking surface UD/3K, Matt/Glossy ERD: 546mm Weight: 520g/pc
Hubs for Option:	Novatec D711SB/D712SB , 407g/set Novatec D771SB./D772SB, 407g/set DT Swiss 240S (J-bend/Straight pull, Central Lock / 6 bolt) DT Swiss 350S Straight pull, central lock, 395g/set
O.L.D:	9mm*100mm, 10mm*135mm or 15mm*100mm, 12mm*142mm
Cassette Body:	Shimano 8/9/10/11s XX1, XD freehub is available Campagnolo 10/11s
Spokes for Option:	Sapim cx-ray spoke, Black (267g/set, 56pcs) Sapim cx-delta spoke, Black (267g/set, 56pcs)
Nipple:	Sapim Sils (Aluminium or Brass) Black or red. External or internal.
Lacing:	Standard: Standard: Front--3X, Rear non-drive side--3X, Rear drive side--3X Customized lacing is available
Other Specs:	Roundness: <0.2mm Offset: <0.2mm Max Tension: (Rim)300kgf, (Spoke); F:95kgf, R130kgf Max pressure(Clincher)145psi/10bar, (Tubular)125psi/8.6bar. Max Recommended Rider Weight: 100kgs

FSC38-CM-25 (38x25mm clincher, cyclocross)

Rims:	38mmx25mm full carbon clincher for cyclocross 28H/28H (24H/24 & 32H/32H for option) No braking surface UD/3K, Matt/Glossy ERD: 572mm Weight: 480g/pc
Hubs for Option:	Novatec D711SB/D712SB , 407g/set Novatec D771SB./D772SB, 407g/set DT Swiss 240S (J-bend/Straight pull, Central Lock / 6 bolt) DT Swiss 350S Straight pull, central lock, 395g/set
O.L.D:	9mm*100mm, 10mm*135mm or 15mm*100mm, 12mm*142mm
Cassette Body:	Shimano 8/9/10/11s XX1, XD freehub is available Campagnolo 10/11s
Spokes for Option:	Sapim cx-ray spoke, Black (267g/set, 56pcs) Sapim cx-delta spoke, Black (267g/set, 56pcs)

25mm Cyclocross Full Carbon Clincher

Nipple:	Sapim Sils (Aluminium or Brass) Black or red. External or internal.
Lacing:	Standard: Standard: Front--3X, Rear non-drive side--3X, Rear drive side--3X Customized lacing is available
Other Specs:	Roundness: <0.2mm Offset: <0.2mm Max Tension: (Rim)300kgf, (Spoke); F:95kgf, R130kgf Max pressure(Clincher)145psi/10bar, (Tubular)125psi/8.6bar. Max Recommended Rider Weight: 95kgs