



Environment Test Chamber

TECHNICAL SPECIFICATIONS

Test Space Capacity	50 lts to 8000 lts
Temperature Range	-70°C to +180°C ±1°C
Rate of Change of Temp.	1°C/minute, 5°C
	and 10°C/minute
Performance	Conforms to IS 9000,
	JSS 55555, 50101,
	IEC 68, MIL-STD-202,
	810, 883, DEF-STD-133
	specifications





Rain Test Chamber

TECHNICAL SPECIFICATIONS

Test Space Capacity	216 lts to 8000 lts
Performance	Conforms to IS 9000,
	JSS 55555 and
	IS 2147, IS 10236
	specifications









Dust Test Chamber

TECHNICAL SPECIFICATIONS

Test Space Capacity	216 lts to 8000 lts
Temperature Range	5°C above ambient
Performance	Conforms to IS 9000,
	JSS 55555 and IS
	2147, IS 10236
	specifications.















PRIME ENVIROTECH GREEN ASSURANCE SYSTEM

6 phases for prime envriotech GAS (GREEN ASSURANCE SYSTEM)

secures environmental protection:

- green design
- green procurement
- green manufacturing
- green sales
- green service
- 3R (reuse, recycle and recovery)



6 phases for prime envirotech gas (GREEN ASSURANCE SYSTEM)











VERSATILE & FLEXIBLE PRODUCT RANGE:

- Environmental Chamber
- Thermal Shock Chamber
- Altitude Chamber
- Humidity Chamber
- Sand & Dust Test Chamber
- Corrosion Test Chamber
- Solar Radiation Chamber
- Rain Test Chamber
- Water Bath Chamber
- Walk-in Chamber
- Stability Chamber
- Hypoxia cum Decompression Chamber
- Vibration Test System





Maintenance Contact (AMC) beyond the warranties. Our promptness saves the money and time of the customer. Some of the highlist of extended services includes: High Quality customer support 24 hrs x 7 days "Service hot-line" Installation and Commission Operation and parts warranty application guidance.

Do you have a specify product in mind? Draw out the specifications and hand them over to our nearest sales representatives.

Our website contains all information about the company and products listing and their specifications, technology updates and current news. Just fill up the feedback form and get immediate response.

WHY ENVIRONMENTAL TESTING



Environmental
testing is a mandatory
requirement because it
involves safety and
reliability - not only of
products but also of life.
Market reputations are
gained or lost because of
performance.

OUR BRANCHES IN INDIA:





Khasra No. 31/1, Krishnanagar Lane No.-13, Roorkee - 247 667 Distt. Haridwar (Uttarakhand) Telefax-01332-260887

Mob.: 7037700051

E-mail: info@primeenvirotech.in E-mail: primeenvirotech@yahoo.com Customer Care No.: +91-9568606006