



BATTERY POWERED PET STRAPPING TOOL

Model	PP 101 BPT
Strap Width (mm)	13-16 adjustable
Strap Thickness (mm)	0.5-1.0
Weight (kg)	3.9
Size (LxWxH) (mm)	375x130x140
Tension (kg)	40-200
Type of Seal	Friction Weld
Battery	Up to 200 cycle with one battery charge



CONTINUOUS BAND SEALER

Model	PPCS 770H
Voltage (V/Hz)	220 / 50
Power (W)	650
Sealing Speed (m/min)	0 ~ 12 (0.16)
Sealing Width (mm)	8 ~ 10
Temperature range (Deg.C)	0 ~ 300
Distance from the sealing center to the conveying table (mm)	10 ~ 40
Conveyor size (LxW)mm	840 x 153
Film Thickness (mm)	0.08
Single Conveyor Loading (kg)	1
Overall Conveyor Loading (kg)	3
Overall Dimension (LxWxH)mm	840 x 380 x 550
Net Weight (kg)	32

PNEUMATIC PET STRAPPING TOOL

Model	PP 101 PNT
Strap Width (mm)	13-12 adjustable
Strap Thickness (mm)	1.0-1.5
Weight (kg)	3.8
Size (LxWxH) (mm)	275X115X130
Tension (kg)	200
Type of Seal	Friction Weld
Pressure	5-7 Bar
Strap Material	PET / PP



CONTINUOUS BAND SEALER

Model	PPCS 770V
Voltage (V/Hz)	220 / 50
Power (W)	650
Sealing Speed (m/min)	0 ~ 12 (0.16)
Sealing Width (mm)	8 ~ 10
Temperature range (Deg.C)	0 ~ 300
Distance from the sealing center to the conveying table (mm)	150 ~ 270
Conveyor size (LxW)mm	840 x 153
Film Thickness (mm)	0.08
Single Conveyor Loading (kg)	1
Overall Conveyor Loading (kg)	3
Overall Dimension (LxWxH)mm	840 x 380 x 550
Net Weight (kg)	37

