


UNIVERSAL SALES AGENCY

696, Reid Road, Opp. SBI Bank, O/s. Panchkuva Gate, Panchkuva, Ahmedabad - 380002
 Tel. (079) 22161042 / 22161048 Mobile  - 99252 31275 Email - (1) unipec.india@gmail.com

w.e.f. Dt. 1/4/2019



All Items
HSN - 3917 3210
GST Rate @ 18 %

STEEL WIRE PVC HOSE (THUNDER HOSE)

(S.S. - Spring Steel Wire Reinforced)
 (Food-Grade Material)



SIZE		Dimension		Wall Thickness (mm)	Working Pressure (kg/cm ²)	Standard Length (mtrs.)	Rates Per Mtr. (Rs.)
in (mm)	in (inch)	Inside (mm)	Outside (mm)				
12	(½")	12.7	18.7	3.0 ± 0.2 mm	9 kg/cm ²	50 / 100	56.00
15	(5/8")	15.8	22.8	3.5 ± 0.2 mm	9 kg/cm ²	50 / 100	80.00
20	(¾")	19.0	26.0	3.5 ± 0.2 mm	6 kg/cm ²	50 / 100	107.00
25	(1")	25.4	33.4	4.0 ± 0.2 mm	6 kg/cm ²	50 / 100	151.00
31	(1.¼")	31.8	39.8	4.0 ± 0.2 mm	5 kg/cm ²	30 / 50	217.00
40	(1.½")	38.1	47.1	4.5 ± 0.2 mm	5 kg/cm ²	30 / 50	266.00
50	(2")	50.8	60.8	5.0 ± 0.3 mm	5 kg/cm ²	30 / 50	378.00
65	(2.½")	63.0	74.0	5.5 ± 0.2 mm	5 kg/cm ²	30	446.00

- > Steel Wire Hose Pipes (Thunder Hose) --> S.S. (Spring Steel) wire between two layers of material.
- > Non-Toxic Material (Food-Grade).
- > Suitable for, Milk, Dairy, Pharmaceuticals, Food & Beverages Applications.
- > Temperature Capacity : Max. Upto 70 Deg. C.



Note:

- * Pressure --> 1 Kg./cm² = 0.98 bar (14.22 psi)
- * Pressure --> 1 Kg./cm² = 735 mm of HG (Vacuum Pressure)
- * Pressure --> 1 Kg./cm² = 394 in H₂O (Vacuum Pressure)
- * Bursting Capacity = 3 x Working Pressure (Approx.) - 3 Times.

*** Actual Photograph**