

## Quattro

**CES Hire Ltd. supplying the trade since 1983** 

## **Utiform Quattro Plastering Machine**

- Mixing pump for pre-bagged plasters and renders with large hopper capacity
- Simple, robust, easy to use and clean.
- Fits through all standard doors, 660 mm wide, narrowest machine on the market
- Mixing tube can be inclined with no loss of dry material to change stator or rotor

## "A Great Labour Saving Machine"



Can be taken apart in minutes for easy transport.

The worm pump transports the material through hoses to the spraygun where it is sprayed on the surface with compressed air.



Strator fixing system

Model	three-phase	single-phase
Conveying output	5 to 50 l/min *	5 to 22.5 l/min.*
Pumping distance	40 m *	20 m *
Pumping height	20 m *	10 m *
Voltage	380 V	220 V

**Pumping pressure** 40 bar max. 40 bar max. Power of mixing motor 5.5 kW 3 kW

Power of feed motor 0.55 kW 0.37 kW. (220 V)

Air compressor 250 l-min, 5 bar, 0.9 kW 0.75 kW - 220 V-170 l/min.

continuous air

Water pressure required 3 bar 3 bar

220 V-50Hz 25 A **Electrical connection** 400 V-50Hz 3

 $(5x2.5mm^{2})$ P+N+T 32 A/6h

Size LxWxH (mm) 1100 x 660 x 1455 1100 x 660 x 1455

Weight 215 Kg 205 Kg Loading height 870 mm 870 mm



## **Standard Equipment:**

- Automatic stopping system
- Water pump
- Tool Kit
- Spray gun
- Mixing shaft
- Cleaning tools
- Warranty Certificate
- CE Certificate
- Parts book and manual



**POWER • EFFECIENCY • QUALITY • DESIGN** 

**Binders Industrial Estate** Cryers Hill High Wycombe Bucks HP15 6LJ

edepends on the consistency, quality and composition of the material, diameter and length of delivery hose and pumping the material height.