

Main Features

- Multiple functions including torque setting, unit setting, mode setting, data storage, data clear, data output and online calibration.
- 9 pre-settable target torque values.
- Functions in both clockwise and anticlockwise directions.
- LCD display showing N-m, ft-lb, in-lb and kg-cm measurements.
- Audible and visible torque confirmation by means of buzzer and 12 LED display.
- Data memory size 50 or 250 optional.
- 250 data memory points with PC connectivity for data download (software included)



Model No.	WE2-030BN	WE3-135BN	WE4-200BN	WE4-340BN	WS3-060CN	WS3-135CN	WS4-200CN
	WK2-030BR	WK3-135BR	WK4-200BR	WK4-340BR			
Measured Torque Range	1.5-30Nm 1.11-22.12 ft-lb 13.3-265.5 in-lb 15.3-306 kg-cm	6.8-135 Nm 5-99.5 ft-lb 60-1195 in-lb 69-1378 kg-cm	10-200 Nm 17.4-147.5 ft-lb 88-1770 in-lb 102-2041 kg-cm	17-340 Nm 12.5-250.7 ft-lb 150-3009 in-lb 173-3469 kg-cm	3-60 Nm 2.21-44.24 ft-lb 26.5-530.9 in-lb 30.6-612 kg-cm	6.8-135 Nm 5-99.5 ft-lb 60-1195 in-lb 69-1378 kg-cm	10-200 Nm 17.4-147.5 ft-lb 88-1770 in-lb 102-2041 kg-cm
Resolution	0.01Nm 0.01 ft-lb 0.1 in-lb 0.1 kg-cm	0.1Nm 0.1 ft-lb 1 in-lb 1 kg-cm	0.1Nm 0.1 ft-lb 1 in-lb 1 kg-cm	0.1Nm 0.1 ft-lb 1 in-lb 1 kg-cm	0.01Nm 0.01 ft-lb 0.1 in-lb 0.1 kg-cm	0.1Nm 0.1 ft-lb 1 in-lb 1 kg-cm	0.1Nm 0.1 ft-lb 1 in-lb 1 kg-cm
Sq. Drv. (in)	1/4	3/8	1/2	1/2	3/8	3/8	1/2
Length (mm)	390	415	530	650	225	380	500
Accuracy	CW : ±2%; CCW : ±3%				CW : ±3%; CCW : ±4%		
Pre-Setting No.	WE : 1 Set; WK : 9 Sets				1 Set		
Head Type	Lever Type Ratchet				Round Head Ratchet		
Bright LED	WE Series - 12 LD (4 Red + 8 Green) WK Series - 12 LD (2 Red + 10 Green)				6 LED (2 Red + 4 Green)		12 LED
Battery	AA X 2				AAA X 2		AA X 2
Battery Life	110 hrs (continuous) ; 1 year (standby)						
Unit Selection	Nm, in-lb, ft-lb, kg-cm						
Operation Mode	Peak hold / Track						
Operation Temp.	-10°C - 60°C						
Drop Test	1m						
Vibration Test	10G						

** WK Series is with PC Connectivity and 250 Data Memory Size.

**850Nm & 1500Nm Torque Wrench Available on Request

MINI DIGITAL TORQUE WRENCH & DIGITAL SCREWDRIVER



DM Series

BM Series (Bits)



SP Series

Model No.	BM2 - 006BN	BM2 - 012BN	BM2 - 020BN	SP-05BN	SP-2BN	SP-4BN
	DM2 - 006BN	DM2 - 012BN	DM2 - 020BN			
Torque Range	0.3 - 6 Nm	0.6 - 12 Nm	1 - 20 Nm	2.5 - 50 cNm	10 - 200 cNm	20 - 400 cNm
Accuracy	CW : ±3%; CCW : ±4%			CW : ±2.5%; CCW : ±3.5%		
Head Type	BM Series - Bit Type (1/4" Hex) ; DM Series - 1/4" Square Drive			Bit		
Unit Selection	Nm, in-lb, ft-lb, kg-cm			cNm, in-lb, kg-cm		
Bit End (inch)	1/4					
Pre-Setting No.	9					
Bright LED	2 LED (Red + Green)					
NUAGE	Yes					
Battery	AAA x 1					
Data Memory Size	50					

DIGITAL ANGLE TORQUE ADAPTOR & ANGLE METER



AD Series



AM Series



Model No.	AD2-030CN	AD3-135CN	AD4-340CN	AM Series
Torque Range	1.5 - 30 Nm	6.8 - 135 Nm	17 - 340 Nm	
Torque Accuracy	CW : ±3%; CCW : ±4%			
Angle Accuracy	±2° (rotating 90° at a speed of 30°/sec)			± 1°
Pre-Setting No.	9			
Bright LED	2 LED (Red + Green)			
Data Memory Size	50			

ANGLE TORQUE WRENCH

AWK Series



Torque Range: 10-200 Nm
 7.4-147.5 ft-lb
 88-1770 in-lb
 102-2041 kg-cm
 0-360°

Model No.	Sq. Drv.	Torque Accuracy	Length Accuracy
AWK-200 BN	1/2"	CW : ±2% CCW : ±3%	±2°

DIGITAL ADJUSTABLE SPANNER

WKA Series



Torque Range: 6.8-135 Nm
 5-99.5 ft-lb
 60-1195 in-lb
 69-1378 kg-cm

Model No.	Accuracy	Open End Size	Length
WKA10-135CN	±3%	31mm	525 mm

INTERCHANGEABLE HEAD TORQUE WRENCH

WPC Series



Torque Range: 4.2-85 Nm
 3.1-62.7 ft-lb
 37-752 in-lb
 43-867 kg-cm

Model No.	Sq. Drv.	Torque Accuracy	Length
WPC3-085BN	3/8"	CW : ±2% CCW : ±3%	271 mm

INTERCHANGEABLE HEAD TORQUE WRENCH

WKC Series



Torque Range: 10-200 Nm
 7.4-147.5ft-lb
 88-1770 in-lb
 102-2041 kg-cm

Model No.	Sq. Drv.	Torque Accuracy	Length
WKC4-200BN	1/2"	CW : ±2% CCW : ±3%	545 mm

ROUND HEAD RATCHET INSERT

Model No.	Sq. Drv. (in.)	Size of End Fitting
EQ-3012113	1/4	9x12mm
EQ-3013113	3/8	9x12mm
EQ-3014116	1/2	9x12mm
EQ-3014117	1/2	14x18mm



EQ-3013113



EQ-3014117