

RER GRADE

For decorative and PVC Substrates



Product Overview

General Properties

This foil is mainly using for uncoated and rough Paper. It has a good adhesion strength and moisture resistance. This foil is a fine choice for application combining Foiling with Embossing.

Main applications

Uncoated Paper, Rough paper and Board

Key Features

This foil has easy release characteristic with good Rub and Abrasion resistance in graphic application. This foil is suitable for large image area on uncoated Paper

Technical information

Shades availability - RER grade is available in dark shades of gold

Operating temperature - Platen 80 to 120 degree Celsius
Cylinder 105 to 135 degree Celsius
Rotary 140 to 180 degree Celsius

Resistance property - Moisture resistance
Rub and Abrasion resistance.
High UV resistance
Scratch resistance

Storage conditions - Temperature 18 to 35 degree Celsius
and 35 to 70% relative humidity

Toxicity - RER Grade is classed on Non-toxic meeting
Stringent legislation of numerous national
and international industry standards including

ICP Ms Method
EN 1122 by ICP Ms
ASTM - D 3421:75

www.rasikfoils.com

141Kms, Delhi-Agra bypass road, Near alwar railway bridge, Krishna nagar, Mathura (U.P), India 281004
Phone +91-565-2423365 Mobile +91-9927022764