

TECHNICAL DATA SHEET

BILTREAT 5815 S **(Medium – High Charge Flocculant)**

Description:

- BILTREAT 5815 S is medium charge cationic powder flocculant with high molecular weight used for retention & drainage including ETP.

Physical Properties:

Appearance	White to off white powder
Generic Name	Copolymer of Acrylamide/Ethanaminium N,N,N-trimethyl-2-(1-oxo-2-propenyl)oxy chloride
Ionic Character	Cationic
Charge Density	Medium
UL Viscosity (cps)	4.0 – 5.0
% NVS	85 – 95
Storage Temperature °C	0 °C – 35 °C

Handling & Storage:

- Avoid contact with skin & eyes. Keep in a cool dry place. Keep away from heat & sources of ignition. Freezing will affect the physical condition & may damage the material, when stored inside a building at a stable temperature between 5° C and 30°C.
- For further technical assistance, please refer MSDS.

Packing:

- BILTREAT 5815 S is supplied in 25 kg HDPE bags.

Shelf Life:

- 1 year from the date of manufacturing.

Disclaimer: The suggestion & data in this publication is currently believed to be accurate. We do not guarantee its accuracy as the conditions & methods of the use of our products are beyond our control. Purchasers should always make their own determination of its suitability and completeness for a particular use, for the protection of the environment & for the health and safety of employees.