

DIPOLE™

Powder Coating Systems

Technical Data :-

- ★ Weight of Gun : 500 gms
- ★ Frequency : 17 KHz.
- ★ Voltage Out put : 90 KV
- ★ H-V Engagement Mode : Inside Gun
- ★ Air Consumption : Max. 13 Nm³/hr
- ★ Power Consumption : 30W
- ★ Max. Current Output : 125 μAmp
- ★ Power Source : 220/240V (AC)
- ★ Voltage Input : DC/24V (12-0-12)
- ★ Polarity : Negative
- ★ Max. Injection Capacity : 650 g/min



VENTURI PUMP
VT 03



SG 05

Also available :- Exceptional concept of **Outside Path – External Powder Way** Electrostatic Spray Gun for giving enriched charging with better powder flow, no powder choking / trapping as compared to inside powder path guns.

Features :-

- ★ Fast & easy colour change Extremely Useful with its External Powder Way/ Path.
- ★ Metallic Powder specialist. Helps in coating metallic powder more efficiently as compared to other models.

DIPOLE™

Powder Coating Systems

MODEL AYRA N801-Extreme

New Design & lighter weight Gun with Easy Clean Modular design for optimum efficiency, exceptional performance. 500 gms Gun Weight

- Maximum Operating Safety / Easy Maintenance
- Automatic Voltage Fold Back – HV Voltage & Current reduce as the gun goes nearer to the article.
- Low Faraday Cage Effect.
- Superb Charging at the tip of the gun – Maximum transfer efficiency upto 75%.
- Flexible Cord with Silicone Rubber pipe for Powder outlet.
- Optional Nozzles (Flat-Round-Four Way) / Deflectors in different pattern are parts of standard equipment.
- New Integral-power-supply technology for higher efficiency & versatile performance. Auto Failure Control.
- New Stainless Steel Hopper easy to clean / corrosion free. Available in 10 Kgs, 15 Kgs & 25 Kgs. Capacity
- New Powder Control Block / pump for better powder flow & longer venture life.

DIPOLE™
AYRA N801-Extreme

